Hydraulic 4-Ram-Lift

Type: JAB QuattroRam 65 AN-S2





The QuattroRam 65 AN-S2 offers two independent lifts at only one workstation, which makes it suitable for all kind of workshop demands. Due to the secondary stroke with swing arms the lift is suitable for service reception as well as repair works.

With the 5.500 mm long drive-on platforms with a lifting capacity of 6.500 kg the vehicles can be lifted at the wheels. Together with the 2-stage telescopic swing arms as secondary stroke, wheel-free lifting of vehicles is possible as well.

In combination with very short lifting and lowering time, this lift is predestinated for the service reception. Due to its design with round rams, the lift is perfectly protected against infiltration of humidity and liquids.

Technical Data

Туре	QuattroRam 65 AN-S2
Lifting capacity	6.500 kg
Ram distance length/cross	1.500/4120 mm
Effective stroke	1.980/2.240 mm
Lifting time approx.	50 sec.
Electric motor	3 x 2 kW
Oil filling	3 x 10 ltr.

JAB-Advantages:

- Foundation cassettes and installation frames separately, only screwed together
- All force is taken up by the installation frame and led into the ground
- Extremely low drive-on height of approx. 160 mm
- Very fast lifting of vehicle
- Environmental friendly through low oil quantity and use of bio-degradable hydraulic oil (upon request)
- Easy to maintain through best accessibility
- Highest quality and huge life span
- Many accessories for all kind of demands
- ` Advice, after-sales and maintenance all through

In case you need any further information, please don't hesitate to contact us!

JAB — Made in Germany







Detailed dimensions

Type: JAB QuattroRam 65 AN-S2







